

## TECHNICAL SPECIFICATIONS

- Operates on 150-230V cooling signal
- Self-priming lifts 3 metres
- 12 metres discharge head
- Water flow rate: 6.25 ltrs per hr @ 12 metres head
- 3 minute timer overrun
- No siphoning back
- No loud sound from dry running
- Pumps water, fibrously contaminated water and air
- Manual test switch
- Pump rating: 0.2A, 230V AC  
Alternative voltages available
- Fire retardant plastics
- Inlet/outlet size: 6mm
- Push-in plug
- Wall-mounted bracket

### INSTALLATION NOTES

Connect the pump to the appropriate drip tray (using the vinyl tube supplied), then connect to the mains power supply, and control link to the air-conditioning units cooling signal.

**PLEASE NOTE: The signal wire must be connected to the cooling signal only. This ensures that when the system is on heating, the pump does not run.**

The pump is designed to sit level on its base and MUST at all times have adequate space around it for good ventilation.

Ensure that there are no kinks or trapped parts in the piping, which must have a 6mm I/D and 9mm O/D. Fix the pipes with cable ties to the pump inlet and outlet.

A variable connector is provided to make easy installation between the condensate tray outlet and vinyl tube.

All the peristaltics now come with a wall-mounted bracket which is designed to hold a replacement head tube for your servicing convenience.



### SERVICE GUIDE

We recommend that you inspect the pump head regularly, and change the pump head tube every 12 months or more frequently if required.

### ELECTRICAL CONNECTIONS

<b>Brown</b>	Live
<b>Blue</b>	Neutral
<b>Green/ Yellow</b>	Earth
<b>Black</b>	Switched live from signal

### PUMP DIMENSIONS

Product	Height	Width	Depth	Weight
<b>STANDARD</b>	142mm	160mm	83mm	1.5kg



## The Standard peristaltic pump is triggered by the hard-wired cooling signal from the air conditioning unit.

The Standard is designed to fit in ceiling voids and lift the condensate water from wall mounted machines where a gravity drain is too obtrusive. It can also be used on cassettes fitted with an internal lift pump.

The pump can be mounted remotely as it is self-priming to a height of 3 metres and will pump 6.25 litres of water per hour against a maximum head of 12 metres.

The pump runs constantly while the air conditioning system is cooling – when the cooling switches off a 3 minute timer ensures that the condensate tray is emptied before the pump switches off. Rollers in the pump act as check valves to stop the condensate draining back into the condensate tray.

The Standard pump is a peristaltic rotary type - which means that it is quiet in operation, very reliable and will run dry without fear of damage or embarrassing noise. Unlike other pumps using either mechanical or electrical conductivity sensors, the Standard does not suffer from corrosion or contamination problems.